

Concord Road Equipment Mfg., Inc.
Painesville, Ohio 44077
1-800-942-ROAD (7623)

CRE 100 Series Undertailgate Gravity Feed Chip Spreader

Specifications

Standard Equipment and Features Include:

All heavy duty all steel construction
Hopper end plates constructed of 1/4" steel plate, hopper perimeter rails constructed of formed channel, 1/4 inch thick
20 inch overall hopper height, 28 inch overall hopper width
Hopper front and rear walls constructed of 3/16" steel plate
Adjustable main door has operating handles at both ends
One piece main sliding door constructed of 3/16" steel plate, adjustable with a maximum opening of 4 inches
Sliding door reinforced with 1/4 inch thick, 2 inch x 2 inch structural steel angle
Sliding door pivot cross shaft constructed of 1-1/2 inch schedule 40 pipe
Sliding door pivot cross shaft extends the full length of hopper trough and through end plates
Front frame stops constructed of 1/4 inch thick, 6 inch formed channel
Hopper upper end plate reinforcements constructed of 1/8 inch thick formed channels
Spread width cut off gates are manual lever controlled, each 12 inches wide and constructed of 1/8 inch thick plate
Unit comes complete with three adjustable legs for storage and easy transfer between trucks
Adjustable legs constructed of 2 inch by 2 inch square tubing with a 3/8 inch diameter pin
Mounting kit includes two hanger pulley assemblies, two hopper mounted worm gear winches with 10 ft wire cable, and two dump body bolt-on brackets
Complete assembly comes primed and painted Omaha Orange

Two Models to Choose From:

CRE-108CS - 108 inch maximum spread width model

9 ft overall hopper spread width
9 manually adjustable spread width cut off gates

CRE-120CS - 120 inch maximum spread width model

10 ft overall hopper spread width
10 manually adjustable spread width cut off gates

Optional Equipment:

CRE-100-AOD - Air operated main door

Available on both the 108 and 120 inch models, the air operated main door allows the operator to start and stop spreading with the flip of a switch, includes a hand held pendant with 15ft self retracting cord

* Requires air supply and 12 volt DC power